



Angående placering se 18W-22.050

tilpasses efter pos.5

hul bores efter sammensvejsning af pos.7 og 8

1	bøsning A 60/70 x 30 n.bl. 254	10	se stkl.	6995/13
2	atstivning Hj. 65 x 8	9	st. 37	200
2	ring 10 mm pl.	8	"	320 x 160 x 10
1	10 mm. pl. til leje	7	"	315 x 170 x 10
1	13 mm. pl. til leje	6	"	250 x 170 x 13
1	U-jern 160 x 65 x 7.5 x 10.5	5	"	250
1	vinkeljern 100 x 100 x 12	4	"	155
1	" 65 x 65 x 7	3	"	345
1	" 75 x 75 x 8	2	"	2255
1	vinkeljern 75 x 75 x 8	1	st. 37	1970

TEGN. EU. 14-12-50	REV. 24-6-54 CWA	174	II-L	Målestok: 1:10, 1:5
Kalk. B.S.	Norm.			
Dato	Rettelser	Indeks		FRICHS Stykliste nr. 6984 Tegningens nummer 18W-22.056.
13-5	Pos. 2 og pos. 9 ændret ny tegn.	CWK	A	
Anvendelse				Indeks: A
Diesel-el.500/550 hk.motorvogn.				
Tegningens benævnelse				
Fast punkt til bremsearm for motorbogje.				