



| | | | | | | |
|----|---------------------|------|----|--------------------|--|------|
| 2 | W. 25x25x3 | rel. | 29 | F.L.E. | | S.L. |
| 2 | Bleche | | 28 | " | | L |
| 2 | Bleche | | 27 | " | | L |
| 50 | Schrauben 7/8" | | 27 | F.L.E. (Ver. 101°) | | |
| 6 | " 3/8" | | 25 | " | | M5 |
| 8 | " 1/2" | | 24 | " | | M5 |
| 32 | Schrauben 7/8" | | 23 | " | | M5 |
| 14 | Winkelstücke | | 22 | " | | L |
| 2 | K.E. 30x30x4 | | 21 | " | | |
| 2 | " 30x30x4 | | 20 | " | | |
| 2 | " 25x25x3 | | 19 | " | | |
| 2 | " | rel. | 18 | " | | L |
| 2 | " | | 17 | " | | |
| 2 | " | rel. | 16 | " | | |
| 2 | " | | 15 | " | | |
| 4 | " | rel. | 14 | " | | S.L. |
| 4 | W. 25x25x3 | rel. | 13 | " | | S.L. |
| 2 | Hinterbleche | | 12 | " | | |
| 2 | Zwischenbleche | | 11 | " | | |
| 2 | Böden | | 10 | " | | |
| 2 | Untere Bleche | | 9 | " | | |
| 2 | Obere Bleche | | 8 | " | | |
| 2 | Hinterwände | | 7 | " | | |
| 2 | Vorderwände | | 6 | " | | |
| 2 | Rußwände | | 5 | " | | |
| 2 | Paßbleche gefüllt | rel. | 4 | " | | |
| 2 | Ausströmhöhle | rel. | 3 | " gerade | | |
| 2 | Einströmhöhle unten | " | 2 | " auswärts | | |
| 2 | Einströmhöhle oben | rel. | 1 | F.L.E. bestellt. | | |

| c | b | a | Benennung | Teil | Werkstoff | Bemerkungen | Modell od. Zeichn. | Werkzeug od. Abdruck | roh fertig | Arbeitsleistung |
|---|---|---|-----------|------|-----------|-------------|--------------------|----------------------|------------|-----------------|
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

HENSCHEL & SOHN G.m.b.H.
CASSEL.
Abteilung - L.B.III

Maßstab 1:1 1:5 Maß in mm Ursprung 20.4.85/88
Dampf- & Ausströmhöhle und Bekleidung

66