1 Stck. Doppel-Schl. m. 45 m/m Schlw. 3
1 " Einfache " " 45 " Schlw. und 290 m/m Schaftl. 9
1 " " " 40 " " 260 " " 10

1 Stck. Doppel-Schl. m. 35 & 30 m/m Schlw. 4
1 " Einfache " " 35 m/m Schlw. und 240 m/m Schaftl. 11
1 " " " 30 " " 220 " " 12

nach punkt. Linien

1 Stck. Doppel-Schl. m. 25 - 21 m/m Schlw. 5
1 " Einfache " " 25 m/m Schlw. & 240 m/m Schaftl. 13
1 " " " 21 " " & 180 " " 14

1 Stck. Doppel-Schl. m. 21 u. 16 m/m Schlw. 6
1 " Einfache " " 16 " " und 150 m/m Schaftl. 15

1 Stck. Doppel-Schl. m. 21 u. 16 m/m Schlw. 7
1 " Einfache " " 16 " " u. 150 m/m Schaftl. 16
" " Schaftlänge " " " 120 " 17

nach punkt. Linien

Ausführung für eine Lokomotive					Material-Bestellung für eine Lokomotive		Fertig-Gewicht
Stückzahl	Benennung	Nummer	Material	Bemerkung	Bestellnummer	Dimensionen und Modell-Zeichen	kg:
1	Schraubenschlüssel	1	Sch.-E.				
1	" "	2	"				
1	" "	3	"				
1	" "	4	"				
1	" "	5	"				
1	" "	6	"				
1	" "	7	"				
1	engl. Schraubenschlüssel	8	" "				
1	Schraubenschlüssel	9					
1	" "	10	"				
1	" "	11	"				
1	" "	12	"				
1	" "	13	"				
1	" "	14	"				
1	" "	15	"				
1	" "	16	"				
1	" "	17	"				

HENSCHEL & SOHN
CASSEL

Schraubenschlüssel

zu den 16(½) Heissd. Tende: Lokomotiven

für die Holding. Südbahnen, Holding.

Fabr. No. 10696/6. Zeichnung No. 226