



wiren tilpasses således, at jalousiet er lukket, når sikringen er i yderste hul.

1	båndtag, 26 x 10 x 110	23	st. 00	flj. 26 x 10 x 120.
2	skruer halv. h. m. møtr. 5 M8 x 25	22	st. 34	magasin
6	split 2 x 12 D5172	21	udgl. st.	"
1	split 5 x 45 D5172	20	udgl. st.	"
1	konisk stift 5 x 36 D5171	19	st. 60	"
1	møtrik 4 M8	18	st. 34	"
1	skruer m. halv. h. 4 M8 x 10	17	st. 34	magasin
1	kæde C.F.P. kalf. nr. 0 556/22	16	messing	L = 160
	bindetråd	15		magasin
1	bindestrømmer 1/4" C.F.P. kalf. nr. 0 335/4	14	galv. jern	magasin
2	wirelås flj. 22 x 6,5 x 12	13	st. 00	flj. 22 x 6,5 x 30
1	wire 3°	12	st.	L = 5200
3	aksel 8° x 25	11	komprim. st. 00	8° x 105
3	rulle 50° x 9	10	messing	50° x 45
2	afstandsstykke 26 x 10 x 14	9	st. 00	flj. 26 x 10 x 35
1	føring 126/74° x 10	8	"	130 x 130 x 10
1	bøjle 20 x 3,4 x 121	7	"	båndj. 20 x 3,4 x 135
2	bøjle 20 x 3,4 x 121	6	st. 00	båndj. 20 x 3,4 x 270
1	aksel 16° x 70	5	komprim. st. 00	16° x 75
1	bøsning 32° x 34	4	st. 00	32° x 40
1	nav 32° x 15	3	"	32° x 20
1	wirearm 32° x 10 x 118	2	"	32° x 10 x 125
1	håndgreb 40 x 10 x 190	1	st. 00	flj. 40 x 10 x 195

Stk.	Betegnelse	Pos.	Materiale kvalitet	Model nr. eller materiale størrelse	13	14	15	16	
Tegn.	F.5.5-5-54	Rev.	20.10.64.F.M.	Afd.	EL.				
Kalt.	R.5.23-10-54	Vorm.		Dato					
Dato		Rettelser		Indsats					
1/2	Pos. 1 og 23 forkræbet 25mm.			CR					
1/2	Pos. 19 var for 3 x 36.			b					
Målestok: 1:10, 1:25, 1:1									
Diesel-mek. 167/183 hk. rangertr.					FRICHS				
Træk for jalousi.					9858				
304L-25.571									