



55145-2

1	1	SVøb	1500 ØV. 3	Plumbr.	3.100
2	2	Skulptplade			
3	2	Plade			
4	2	Endebund			
5	1	do			
6	1	SVøb for Sump			
7	1	Rasse for Armatur			
8	2	Bund for do			
9	1	Tragt			
10	2	Bærevinkel			365-250
11	4	Afslutning 8mm			Affald
12	2	do			
13	1	Flange	185/150-70		200x200
14	1	do	145/100-60		x 8
15	1	Dæksel	185/150		200x200
16	1	do	145/100		x 8
17	2	Rørbenning	50/65		
18	1	Rørsk.			x 1400
19	1	do			
20	14	Brusttop	3/8-42		150x660
21	6	do	3/16-36		120x250
22	2	Flange	65x		6W 16.48
23	4	do	108x80x12		157 19.165
24	2	Studs	1 1/4 60x		6W 16.01
25	2	do	1 3/8		12.6L 1.47
26	2	Nippel i Alum.	1/2 20x		60x60 50.0.70
27	2	do	3/8 20x		60x60 40.0.70
28	28	Spændeskive	3/8		20x200
29	28	Møtrik	3/8		Udsk. Møtrik
30	6	do	5/16		
31	2	Vinkel	3/4 20x		6.5 40
32	1	do	1		
33	1	Patning	1 1/2 150x		60x60 200x200
34	1	do	1 1/2 100x		
35	1	1.50x Vandstandsarmatur			1.50x Vandst.
36	1	Vandstandsglas			1.50x Vandst.

Obs! Bemærk monteringsvejledning

A/S FRICHS EARNUS

Kølevandsbeholder 430 Liter

Diesel ol. motor til Motorolje

dte

1.5
1.25 128 L 16.01